



ACCESSORIES

SKD-11 FLOW CONTROLLER

FLOW CONTROL SWITCH

SKD-11



Operation and Application

The SKD-11 flow control switch starts the pump automatically when pressure decreases (for example taps are opened) and stops it when there is no flow/water shortage (for example taps are closed). It can be used for drinking water or non-potable water piping systems.

Operating limits



Flow from 0 to 15m³/h
 Pipe Water Temperature 0 - 60°C (not frozen)
 Ambient Temperature 0 - 45°C

Note: Use separate non-return valve with this device.



Technical features

Flow from 0 to 15m³/h.
 Rated Voltage: 220VAC, 50Hz
 Maximum current: 30 A
 Protection grade: IP65
 Starting pressure: 1.2 bar
 Maximum pressure: 10 bar
 Inlet/outlet size: (1¼" x 1¼") BSP

<p>REPLACEABLE PC BOARD</p> 	<p>ADJUSTABLE PRESSURE</p>  <p>cut in pressure adjustable between 1.2 & 1.5 bar</p>
---	---

MODEL	INPUT VOLTAGE	FREQUENCY	CURRENT	POWER		STANDBY POWER
	(V)	(Hz)	(A)	(W)	(HP)	(W)
SKD-11	220	50	30	3300	4.4	16

Sectional drawing

